

Font: Bariol Regular (size 14)

Product Image

Supplied

Product Range (General name / product title)

LED Circular Panel Downlights

Part Number (NL code)

Description (overview of product)

An efficient and practical range of fittings providing the required light levels and excellent savings when compared to traditional halogen or fluorescent equivalent products

Key features

- Ultra-thin and stylish design
- Non-dimmable plug and play driver included
- Loop-in / Loop-out connector provided for reducing the fitting time on multiple installations
- Push and lock design for an easy-fit connection
- Recessed mounted
- Maintenance free
- Available in 4 cut-out sizes

Technical details

Part Number (NL code)
LEDCIRC5

Integral LED Part No
ILDL105A1001

Cut-out Size (mm)
105

Diameter (mm)
120

Depth (mm)
20

Total Power (W)
6

Light Output (lm)
420

Efficacy (lm/w)
70

Colour (k)
5000

CRI
80+

IP Rating
20

Warranty
5 years

Product Finish
White

Optic
Opal diffuser

Material
Aluminium

Voltage Range
220-240V

Current
AC

Dimming
Non-dimmable

CE/RoHS
Yes

LVD Certified
Yes

EN
EN-60598

Part Number (NL code)
LEDCIRC6

Integral LED Part No

ILDL131A1001

Cut-out Size (mm)

131

Diameter (mm)

145

Depth (mm)

20

Total Power (W)

9

Light Output (lm)

630

Efficacy (lm/w)

70

Colour (k)

5000

CRI

80+

IP Rating

20

Warranty

5 years

Product Finish

White

Optic

Opal diffuser

Material

Aluminium

Voltage Range

220-240V

Current

AC

Dimming

Non-dimmable

CE/RoHS

Yes

LVD Certified

Yes

EN

EN-60598

Part Number (NL code)

LEDCIRC7

Integral LED Part No

ILDL160A1001

Cut-out Size (mm)

160

Diameter (mm)

175

Depth (mm)

20

Total Power (W)

12

Light Output (lm)

840

Efficacy (lm/w)

70

Colour (k)

5000

CRI

80+

IP Rating

20

Warranty

5 years

Product Finish

White

Optic

Opal diffuser

Material

Aluminium

Voltage Range

220-240V

Current

AC

Dimming
Non-dimmable

CE/RoHS
Yes

LVD Certified
Yes

EN
EN-60598

Part Number (NL code)
LEDCIRC8

Integral LED Part No
ILDL225A1001

Cut-out Size (mm)
225

Diameter (mm)
240

Depth (mm)

20

Total Power (W)

18

Light Output (lm)

1260

Efficacy (lm/w)

70

Colour (k)

5000

CRI

80+

IP Rating

20

Warranty

5 years

Product Finish

White

Optic

Opal diffuser

Material

Aluminium

Voltage Range

220-240V

Current

AC

Dimming

Non-dimmable

CE/RoHS

Yes

LVD Certified

Yes

EN

EN-60598

Date completed by manufacturer:

29/05/15